

Haralson Crossbody/Belt Bag Supply List

Debi Vanden Heuvel Debi6453@gmail.com

Supplies:

- Pattern: Haralson belt bag by Noodlehead (AG-552)
- Fabric:
 - Exterior – ¼ yard, or FQ if using a contrast flap, 1/3 yard if using one fabric for exterior.
 - Contrast Flap – FQ or 6" x 11" of cork or vinyl
 - Lining – ½ yard or 2/3 yard if directional
- Interfacing:
 - 1 ¾ yard of woven fusible (SF 101)
- Hardware
 - 18" #4.5 or #5 zipper by the yard and 2 pulls
 - (2) 1" D-rings or triangle rings
 - (2) 1" swivel hooks
 - (1) 1" strap slider
 - Closure options: turn lock, magnetic snap, ¾" clasp and d-ring, etc.
- Strap
 - 1 ½ - 2 yards of 1" cotton webbing or seatbelt webbing. (Note: Some cotton webbing at is 1 ¼" wide – adjust hardware accordingly if you want to use that.) It is designed to be worn cross chest. If you want to wear it cross body, you might want your strap a little longer than is stated in pattern.
 - Could also be made of fabric if desired. (Add ¼ yd of fabric and ½ yd of interfacing)
- Polyester thread - NOT cotton - to match exterior and lining.
- Marking pencil
- Rotary cutter and mat
- Microtex, Topstitching, Denim, or jeans needles size 90 and/or 100
- Scissors/snips
- Pinking shears (if you have them)
- Wonder clips or similar.
- 1/8" double stick tape such as By Annie or similar.
- Sewing machine with all of your feet: zipper foot, edge stitching foot (opt) or ¼" foot (opt)

Preparation:

- All cotton fabric should have one layer of SF 101 on it. The pattern suggests a second layer of the same cut inside the stitching lines. You can bump this up a bit with fusible fleece inside the stitch lines, but it can get thick for some machines.
- If you want to cut out your pieces before the first class, that is fine – if you want to wait until the first class, that is fine also. I am available if you have questions!
- Use the enclosed tags to label all pieces.
- Some pieces are pattern pieces, and some are rectangles without pieces. Use the labels!
- I will bring my rivet press with me if you desire rivets on your bag, but they are NOT required.
- Changes:
 - Cut interior pocket lining to 9" x 13" or (2) at 9" x 6.5"
 - webbing for strap connectors at 3.5"
 - Zipper tape for interior pocket to 9" or more